Testing d.o.o., Tržaška cesta 2 SI-1000 LJUBLJANA, SLOVENIA / EU Tel.: +386 1 426 2199, Fax: +386 1 421 0366

E-mail: mail@testing.si

http://www.iectestequipment.eu





T1-93

JET TEST SET WITH FLOWMETER



#### JET TEST SET WITH FLOWMETER

T1-93

### **KEYWORDS**

TEST DEVICE TO VERIFY PROTECTION AGAINST WATER JETS, HOSE NOZZLE, JET TEST SET with FLOWMETER, IEC 60529, IPX5, IPX6 ...

### **COMPLIANCE**

T1-93 JET TEST SET with FLOWMETER is designed and manufactured in compliance with IEC 60529 and many other standards.

http://webstore.iec.ch/preview/info\_iec60529%7Bed2.1%7Db.pdf

# **DESCRIPTION**

JET TEST SET with FLOWMETER is intended for establishing the degree of protection against ingress of water for class IPX5 (Protected against water jets) and IPX6 (Protected against heavy seas).

## **FEATURES**

The JET TEST SET consists of:

- NOZZLE dia. 6,3 mm (IPX5) exchangeable
- NOZZLE dia. 12,5 mm (IPX6) exchangeable
- Handle with isolation against cold
- Valve for water flow regulation and for turning off
- Flowmeter
- Hose connector
- 2 wrenches for nozzle exchange



#### JET TEST SET WITH FLOWMETER

T1-93

## **TECHNICAL SPECIFICATIONS**

Diameter of nozzles 6,3 mm

12,5 mm

Flowmeter 5 – 120 l/min +- 1%

Hose connector 1"

## **DESIGN**

nozzles and handle of stainless steel, valve galvanically protected, packed in wooden box that indicates conformity with IEC standard

The buyer shall check if his water network/tap is able to deliver 100 l/min. That can be done with a bucket of known volume and a timer. If the volume is not known also a scale can be used for same purpose.

# **OTHER CONDITIONS**

Warranty: 2 years

Support by E-mail: <a href="mailto:support@testing.si">support@testing.si</a>

On line Skype VIDEO Support: Testing\_support, matejsimonic

We will be glad to help you and to hear any feedback from you.

The equipment described here is subject to redesign without notice. The change will not impair the function of apparatus its characteristics or the price.